

**Radiological Safety**

**Radiological Survey, RP Field Operations Group, Ext. 4299**

*This section to be completed by RP if the penetration will be within a radiologically controlled area, radioactive materials management area, or accelerator housing. Please allow two days.*

Pre-work survey required     Radiological HEPA vacuum cleaner required

Additional requirements for this penetration:

---

Penetration does not need special requirements. .

Checked by: \_\_\_\_\_


Date: \_\_\_\_\_

**Review, Approval, and Authorization**


Any deviation from the scope of work identified on this permit requires re-validation of this permit. This penetration permit expires 30 days after issuance.

**Class 1 & 2 Authorizations**

I have discussed the hazards and controls with the workers and verified that they are trained/qualified to perform the work.

 \_\_\_\_\_ DATE: 9/16/08  
Responsible line manager/designee signature

**Additional Authorization for Class 2**

 \_\_\_\_\_ DATE: 9/16/08  
Area responsible person (e.g. area or building manager)

Penetration Safety: Penetration Permit

### **Hazards and Required Controls**

May reference JHAM or AHA if hazards/controls are documented there

#### **Hazards**

Type and size of energy sources present (including results from NDT, if used):

NO

Hazards specific to the tools that will be used:

NONE

Work environment hazards (such as moisture, lead, asbestos, etc.):

NONE

Other hazards:

No

#### **Controls**

Procedural requirements:

TOOL INSPECTION, GFCI TESTED

Types and classification of PPE:

GLOVES, SAFETY GLASSES, RRF VEST, & BOOTS

Other controls:

VACUUM

Complete the "Radiological Safety" section if appropriate, and complete the Review, Approval, and Authorization section at the end of this form.

Penetration Safety: Penetration Permit

**Class 2 Penetration Checklist**

Greater than 2 inches into solid material

	Yes	N/A
Reviewed historical records, engineering plans, and drawings?	_____	<u>X</u>
Area responsible person/designee, customer/requester, or other personnel consulted?	<u>X</u>	_____
Visually inspected proposed location of penetration?	<u>X</u>	_____
Checked other side of walls, under floors, or through false ceilings for hazards?	_____	<u>X</u>
De-energized and locked/tagged-out energy sources as required?	_____	<u>X</u>
NDT used to determine if additional hazards exist? <i>If yes, list results under "Hazards."</i>	_____	<u>X</u>
NDT used to determine wall reinforcement?	_____	<u>X</u>
Electrical tools equipped with GFCI or double-insulated?	<u>X</u>	_____
GFCIs tested?	<u>X</u>	_____
Appropriate PPE specified (see page 3) and obtained?	<u>X</u>	_____
PPE inspection(s) up to date?	<u>X</u>	_____
Short drill bits used or equipment marked to limit penetration depth?	<u>X</u>	_____
Penetration is within a radiologically controlled area or a radioactive material management area. <i>If yes, complete the "Radiological Safety" section of the form.</i>	_____	<u>X</u>
Penetration is part of accelerator shielding (for example: the Accelerator Housing Structure, End Station A Hall, Klystron Gallery Floor)? <i>If yes, complete the "Radiological Safety" section of the form.</i>	_____	<u>X</u>
A Radiation Safety Work Control Form (RSWCF) is required for all penetrations that meet any of the following conditions (contact the area safety officer for more information):	_____	<u>X</u>
<ul style="list-style-type: none"> <li>• Into or through non-concrete radiation shielding</li> <li>• Into concrete radiation shielding, with penetration exceeding 2 inches in diameter</li> <li>• Into concrete radiation shielding, with penetration exceeding 6 inches deep</li> <li>• Into concrete radiation shielding where penetration is not re-filled with a dense material (e.g. concrete or steel)</li> <li>• All the way through concrete radiation shielding</li> </ul>		
Checklist completed by: <u>MICHAEL ROGERS</u>	Date: <u>9-15-08</u>	

Complete "Hazards and Required Controls" section.

Penetration Safety: Penetration Permit

Work Request # (if applicable): \_\_\_\_\_ Date Permit Submitted: \_\_\_\_\_

**General Information**

Area/location	Date(s) work will be performed	Job description (location of penetration, material to be penetrated, tools, etc)
LCLS XRAY & FEH	TILL 10-31-08	DRILL 2 1/8" HOLES IN WALLS FOR FUTURE MONUMENTS
Responsible line manager or designee Name/Organization)	Phone #	Other information (e.g., depth of penetration, etc)
CATHERINE LE COCQ	650-926-2335	2 1/8"

**Class 1 Penetration Checklist**

*Hollow walls, ceilings or floors, or 2 inches or less into solid material*

	Yes	N/A
Checked other side of walls, under floors, or through false ceilings for hazards?	_____	_____
Verified stud locations?	_____	_____
Non-conductive tools to be used?	_____	_____
Masonry bits and hand tools to be used for initial penetration?	_____	_____
Drill bit stops or short drill bits (2 inches or less) to be used for solid material?	_____	_____
Electrical tools equipped with GFCIs or double insulated?	_____	_____
GFCIs tested?	_____	_____
Appropriate PPE specified (see page 3) and obtained?	_____	_____
PPE inspection(s) up to date?	_____	_____
Penetration is within a radiologically controlled area or a radioactive material management area? <i>If yes, complete the "Radiation Safety" portion of the form.</i>	_____	_____
Penetration is part of accelerator shielding (for example: the Accelerator Housing Structure, End Station A Hall, Klystron Gallery/Floor)? <i>If yes, complete the "Radiological Safety" section of the form.</i>	_____	_____
A Radiation Safety Work Control Form (RSWCF) is required for all penetrations that meet any of the following conditions (contact the area safety officer for more information):	_____	_____
<ul style="list-style-type: none"> <li>• Into or through non-concrete radiation shielding</li> <li>• Into concrete radiation shielding, with penetration exceeding 2 inches in diameter</li> <li>• Into concrete radiation shielding, with penetration exceeding 6 inches deep</li> <li>• Into concrete radiation shielding where penetration is not re-filled with a dense material (e.g. concrete or steel)</li> <li>• All the way through concrete radiation shielding</li> </ul>		
Checklist completed by: _____	Date: _____	

Complete "Hazards and Required Controls" section.

## Penetration Safety: Penetration Permit

If it is suspected that hidden hazards exist at the point of penetration, relocate the work if possible. If the work cannot be relocated, use non-destructive testing (NDT) devices (ground penetrating radar, x-ray, magnetic, induction, conductive, or other devices and methods) to determine whether additional hazards exist. For hollow structures a pilot hole may be useful to look for hidden utilities. If the penetration is to be made into a solid load-bearing wall, use NDT before performing the penetration to ensure that it does not interrupt wall reinforcement.

## Penetration Safety: Penetration Permit

Department: Electrical Safety Support Group

Program: Penetration Safety

Owner: Program Manager, Electrical Safety Officer, Perry Anthony (Ext. 2039)

Authority: ES&H Manual, Chapter 44, Penetration Safety

### Instructions

A penetration permit is required for all Class 2 penetrations and for those Class 1 penetrations where the hazards and controls are not documented in a routine or non-routine job hazard analysis and mitigation document (JHAM) or similar work authorization document.<sup>1</sup>

*Class 1 penetrations* are defined as any penetration made into hollow walls, hollow ceilings, or hollow floors, or a penetration into solid materials to a depth of 2.0 inches or less; *Class 2 penetrations* as any deeper than 2.0 inches or all the way through solid materials.

All penetrations within a radiologically controlled area (RCA), a radioactive material management area (RMMA), or part of radiation shielding (for example, the Accelerator Housing Structure, End Station A Hall, Klystron Gallery Floor) require a penetration permit with the "Radiological Safety" section of the permit completed by the Radiation Protection Department in ES&H. Please allow two days for Radiation Protection Department review.

In addition a radiation safety work control form (RSWCF) is required for all penetrations that meet any of the following conditions:<sup>2</sup>

- Into or through non-concrete radiation shielding
- Into concrete radiation shielding, with penetration exceeding 2 inches in diameter
- Into concrete radiation shielding, with penetration exceeding 6 inches deep
- Into concrete radiation shielding where penetration is not re-filled with a dense material (e.g. concrete or steel)
- All the way through concrete radiation shielding

Contact the area safety officer for more information.

The completed penetration permit must be kept at the worksite during task. Upon completion of work send the penetration permit to the Electrical Safety Support Group, Mail Stop 20.

### Pre-planning

Workers will evaluate hazards and controls as required for the penetration work to be performed.

Check behind walls, under floors, or through false ceilings to attempt to locate hidden utilities or other hazards (such as asbestos). In most industrial environments, electric wiring is run in metal conduit. However, it is possible for Romex cable or other soft-surfaced electrical wiring to be present within hollow walls of some buildings, especially in some transportable buildings.

Verify metal stud locations by measuring from adjacent studs or by using detection equipment to determine that the metal is not an electric conduit or gas pipe.

1 "Job Hazard Analysis", <http://www-group.slac.stanford.edu/esh/general/hazanalysis/jham.htm>

2 For the form and procedure, see Guideline 14, "Configuration Control of Radiation Safety Systems", SLAC Guidelines for Operations (SLAC-I-010-00100-000), <https://www-internal.slac.stanford.edu/ad/addo/gfo/gfoindex.html>