The use of simulation to optimise the integration of 3D optical metrology techniques and stability monitoring with capacitive sensors into an alignment concept for the assembly of ITER

Brian Macklin (1) Robert Shaw (1) Bruno Levesy (2) Malak Senhadji (3) Arnauld Dumont (4)

(1) ITER International Organization, Cadarache, France

(2) Formerly at EFDA, now at ITER International Organization, Cadarache, France

(3) ASTRIUM,

(4) FOGALE Nanotech Inc.

#### A few words about FOGALE nanotech

Active Measurement of small dimensions with very high accuracy

Particle Accelerators Alignment (HLS/WPS) Telescopes Alignment (Edge Position Sensors and Photogrammetry) Blade Tip Clearance for aircraft engines (High Temperature Capacitive Sensors) Intelligent Anti-Collision Sensors (customized sensors for robots) Glass and other material thickness measurements (Low Coherence Interferometry Lasers ) 3d Profilers









#### Contents





# The ITER project

 International Thermonuclear Experimental Reactor

World's largest nuclear fusion reactor

Tokamak of 30 meters diameter, 12 meters height, made of 9 sectors weighting at least 1500 tons

Based in Cadarache (South East of France)



Vacuum Vessel (VV)

# Toroidal Field Coil (TFC)

#### Tokamak Assembly in Pit

# FOGALE nanotech Inc.



# JET : Joint European Torus

### **FOGALE** nanotech Inc.



# The Final Alignment Goal

•2 mm Alignment between the magnetic center (with respect to Toroidal Field Coils) and the Vacuum Vessel center,

• The first System Axis is fixed by the Pit Cylinder Best-Fit,

The final one is fixed by the As-Built position of the TFC,

- Measurement Accuracy close to 0.2 mm,
- The Method should take into account :
  - Visibility problems,
  - Stability Issues.

#### Metrology for Assembly Pit Network : Photogrammetry





IWAA08-Tsukuba February 11-15, 2008

#### Metrology for Assembly Sectors Positioning and Assembly : Laser Tracker



IWAA08-Tsukuba February 11-15, 2008

#### •Metrology for Assembly Fiducials on Components



IWAA08-Tsukuba February 11-15, 2008



## •Metrology for Assembly Accuracy considerations

Photogrammetry : Digital : 1/200 000 (1/30th of a pixel) Film Based : 1/500 000 (1.5 µm on image)

Laser Tracker : Angle : +/- 0.6 mgon Distance : 5µm + 5µm/m

## •Metrology for Assembly Accuracy considerations

Network Accuracy
Laser Tracker Positioning and Measurement Accuracy





VV6





#### CERN Results : relative deformation of the ATLAS bedplates during the installation of the Barrel Toroïd System (1600 tons)



"Combined levelling systems for the vertical monitoring of a large physics experiment" CERN

Jean-Christophe Gayde, Andreas Herty, Hélène Mainaud Durand, Christian Lasseur

Metrology for Assembly Stability Survey with an accuracy of a few µm

-4 rings of 9+1 HLS : one ring for each level , one sensor for each sector and one far away as a reference

-9+1 vertical references of 4 WPS : one vertical line for each sector and one with the HLS reference sensors



WPS : Wire Positioning Sensors HLS : Hydrostatic Levelling Sensors IWAA08-Tsukuba February 11-15, 2008





#### The Future

- 1. Outside Topography Network
- 2. Components Manufacturing Control and As-Built Measurements
- 3. Measurement Automation
- Accurate Indoor GPS ?
- Accurate Laser Radar/Scanning?

