

LCLS-II HXU Measurement Results

This report is intended to document the results of HXU segment tuning at LBNL and ANL. It should be sent to SLAC for approval before the HXU segment gets shipped.

Serial number from manufacturers label:	HXU-019
---	---------

Measurement Procedure:

The measurements have been carried out after the undulator segment had been fully tuned according to the “LCLS-II Undulator Test Plan” (LCLS-TN-17-1).

General Hall Probe Scan Evaluation Parameters


Undulator Temperature (should be 20.0)	20.0± 0.5	°C
First core pole #	8	
Last core pole #	253	
Tuning Gap	9.000	mm

Evaluation of Hall Probe Scans at Commissioning Gap

Commissioning Gap Temperature (should be 20.0)	20.1± 0.3	°C
$rms(B_{pk} /⟨ B_{pk} ⟩ - 1)$	0.0027	
K_{eff} at Commissioning Gap (should be 2.3400)	2.3386	
Commissioning Gap	7.93	mm
$I1X$ (over 4.012667 m) (should be within ±40)	25.5	μTm
$I2X$ (over 4.012667 m) (should be within ±150)	-16	μTm^2
$I1Y$ (over 4.012667 m) (should be within ±40)	11.4	μTm
$I2Y$ (over 4.012667 m) (should be within ±150)	129	μTm^2
Phase Shake (rms phase fluctuations over core poles (< 4.0))	2.63	degXray
Cell Phase Advance (over 4.012667 m)	48601.8 (135.005×360)	degXray
Undulator Entrance Phase ¹	2250.0 (25×90)	degXray
Undulator Exit Phase ²	2251.8 (25×90+1.8)	degXray

¹Phase advance from cell start (undulator center -2.006334 m) to center of physical pole 8.

²Phase advance from physical pole 253 to cell end (undulator center +2.006334 m).



Undulator Encoder Settings


USGapEncoderOffset	-457.507800
DSGapEncoderOffset	-4014.486700
USWLinearEncoder.AOFF	93.3828
DSWLinearEncoder.AOFF	93.4616
USALinearEncoder.AOFF	93.5629
DSALinearEncoder.AOFF	94.3340

Undulator Load Cell Readings at Tuning Gap


LC.DAL_FORCE	-190
LC.DAU_FORCE	-29
LC.DWL_FORCE	-115
LC.DWU_FORCE	-88
LC.UAL_FORCE	-75
LC.UAU_FORCE	-14
LC.UWL_FORCE	-10
LC.UWU_FORCE	-87

Undulator Load Cell Readings at 100 mm Gap

LC.DAL_FORCE	0.0
LC.DAU_FORCE	0.0
LC.DWL_FORCE	0.0
LC.DWU_FORCE	0.0
LC.UAL_FORCE	0.0
LC.UAU_FORCE	0.0
LC.UWL_FORCE	0.0
LC.UWU_FORCE	0.0




Evaluation of Hall Probe Scans: K_{eff} vs. gap





Evaluation of Hall Probe Scans: K_{eff} Hysteresis




Plotted functions have been calculated from measured values openKeff (opengap) and closeKeff (closegap) using the following Matlab calculations:

```
Blue Stars: 1-openKeff ./ spline(opengap(2:2:end),openKeff(2:2:end),opengap)
Green Stars: 1-closeKeff ./ spline(opengap(2:2:end),openKeff(2:2:end),closegap)
```




Evaluation of Hall Probe Scans: Phase Shake vs gap






Evaluation of Hall Probe Scans: K_{eff} vs x at Tuning Gap







Evaluation of Hall Probe Scans: K_{eff} vs Y at Tuning Gap






Long Coil Measurement of the On-Axis First Horizontal Field Integrals







Long Coil Measurement of the On-Axis Second Horizontal Field Integrals






Long Coil Measurement of the On-Axis First Vertical Field Integrals







Long Coil Measurement of the On-Axis Second Vertical Field Integrals







Capacitive Sensor Arrangement






Probe1 Capacitive Sensor Readings $y = +5\text{mm}$







Probe2 Capacitive Sensor Readings $y = +5\text{mm}$







Probe1 Capacitive Sensor Readings $y = 0\text{mm}$






Probe2 Capacitive Sensor Readings $y = 0\text{mm}$







Probe1 Capacitive Sensor Readings $y = -5\text{mm}$






Probe2 Capacitive Sensor Readings $y = -5\text{mm}$






Undulator Gap Measurement







Undulator Gap Measurement






Undulator Gap Difference






Undulator Gap Difference







Drive Loads (Gap Opening)




The Forces were only recorded as the gap was closing, and for the gaps that were measured with the Hall Probe.




Drive Load Differences (Gap Opening and Closing)





Strongback Forces, Gap Opening and Closing)





Strongback Force Differences, Gap Opening and Closing

