

SSRL  
B/L 5  
SETTING S-1 DRIFT

6/23/04  
M.R., L.67

Y

HRL 5040

6.927  
57.750  
64.677 ✓  
-43.243 ELEV.  
21.434 ✓  
+ 8.614 @ SLIT  
+ 12.820 VHI @ SLIT

S-1 #1  
12.820  
1.181 Vm.  
11.639 ✓  
(4) .085 Pitch  
11.554 ✓  
1.  
10.554 ✓  
10.554  
0 ✓

P.I.P.E

1.660

✓ 6/23/04  
MR

1.55° SLOPE

PIPE @ SUPPORTS Z - FROM SLIT

Z = 56.5 + 1.528 ✓  
A SLOPE

12.820  
1.528  
11.292 ✓  
.830 RADIUS  
10.462 S/R ✓  
10.452 +010

Z = 102.8 + 2.781 ✓  
B

12.820  
2.781  
10.039 ✓  
.830  
9.209 S/R ✓  
9.206 +003

Z = 150.8 + 4.079 ✓  
C

12.820  
4.079  
8.741 ✓  
.830  
7.911 S/R ✓  
7.907 +004

X -29.528 LOS

A) 29.528

1.830 RAD  
28.698 S/R ✓  
28.560  
28.655 -043

B) 29.528

1.830  
28.698 S/R ✓  
29.69 -002

C) 29.528

1.830  
28.698 S/R ✓  
28.725 +027