

BL7-3
Hutch Stopper

2-22-06
MR, FG

(Y)

<u>1</u>	<u>3</u>	<u>2</u>
21.122	21.122	21.122
<u>3.352</u>	<u>2.844</u>	<u>3.363</u>
17.770 ✓	18.278 ✓	17.759 ✓
<u>1.250</u>	<u>1.250</u>	<u>1.250</u>
16.520 ✓	17.028 ✓	16.509 ✓
<u>1.436</u>	<u>1.436</u>	<u>1.436</u>
S/R 16.084 ✓	S/R 16.592 ✓	S/R 16.073 ✓
15.956	16.531	15.858
16.075 +9 ✓	16.591 +1	16.077 -4 ✓

X)

<u>1</u>	<u>2</u>	⊥ OF STOPPER
29.528	29.528	Z = 698.738
<u>3.820</u>	<u>3.840</u>	3.768"
25.708 ✓	25.688 ✓	
<u>1</u>	<u>1</u>	
24.708 ✓	24.688 ✓	
<u>3.747</u>	<u>3.789</u>	⊥ o/s
20.961 ✓	20.899 ✓	X shift
<u>.375</u>	<u>.375</u>	
S/R 20.586 ✓	S/R 20.524 ✓	
<u>20.600</u> 014	<u>20.525</u> 001	