

SSRL SLIT RB1
 B/L 6-2 TOP



* SHORT ARM *

✓ 8-20-04
 MR

TB	X	Y	Z
A	-2.065 ✓	+8.724 ✓	-0.028 ✓
B	-0.163 ✓	+15.253 ✓	+2.039 ✓
C	-2.194 ✓	+15.207 ✓	-0.005 ✓
D	-0.164 ✓	+15.215 ✓	-2.019 ✓

(4)

RBI

FG
JMc
MP
7-30-04

1/2 mike up .028

1/R .588
Rd .588

8.970 Ref
.028
8.998 = ~~HL~~ BL
29.138
20.140 = HI ✓

A	B	C	D	
10.416	3.887	3.933	3.889	Rd
'	'	'	'	Ft
11.416	4.887	4.933	4.889	
20.140	20.140	20.140	20.140	NI
<u>8.724</u> ✓	<u>15.253</u> ✓	<u>15.207</u> ✓	<u>15.251</u> ✓	

Corrected Values

A	B	C	D
-8.724	-15.253	-15.207	-15.251

BOTTOM SLIT FIDUCIALIZED WITH SMALL FACING UP.
ROTATE ABOUT BEAM LINE.

RB 1

(X)

For Vol .952
 N .952
 1st F 16.446
 N 16.575
 2nd F 18.000
 N 18.033
 S/R 18.534
 LOS - 19.486

FG
 JMc
 MP
 7-30-04

<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	
16.421	18.323	16.292	18.322	Rd
				Ft
17.421	19.323	17.292	19.322	
19.486	19.486	19.486	19.486	LOS
-2.065 ✓	-.163 ✓	-2.194 ✓	-.164 ✓	

Corrected Values

A	B	C	D
+ 2.065	+ .163	+ 2.194	+ .164

RB 1 slit

(Z)

+
LOS

12.888	Rd
1.490	Ft + R
<hr/>	
14.378	✓

FG
JMc
MP
7-30-04

<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	
13.406	11.339	13.383	2.039	BVal
1	1	1	4.058	Caliper
14.406	12.339	14.383		
14.378	14.378	14.378		
-.028 ✓	2.039 ✓	-.005 ✓	-2.019 ✓	