


Included Angle Between Pole Tips

Pole Tip Num. ----->

Angle of Symmetry Line between Pole Tips to Tuning Gap ZX Plane



Dimensions in MM, Angles in Milliradians




HGVPU - Pole Tip Angles

Nominal Gap :	9.000	US Full :	9.0002	DS Full :	9.0004
Nom. Taper :	0.000	US Wall Half :	4.4960	DS Wall Half :	4.5022
		US Aisle Half :	4.4987	DS Aisle Half :	4.5013

S/N	: HXU_026
Date	: 23-SEP-2019
Data Set	: 0001
Run	: FINAL
Cam Pos.	: B

Aisle Pole Mean = 4.499 Aisle Pole Min. = 4.462 Aisle Pole Max. = 4.557 Reg. Line Ang. = 0.010




Aisle Pole Tips at Nom. Beam Height

Blue = Pole Tip points
 Green = Mean line
 Red = Regression line thru points

Pole Tip Num. ----->

Wall Pole Tips at Nom. Beam Height

Minimum Clearance Gap = 8.924



Wall Pole Mean = -4.501 Wall Pole Min. = -4.549 Wall Pole Max. = -4.471 Reg. Line Ang. = 0.010

Girder centerline in reference to Pointed Magnets

Dimensions in MM, Angles in Milliradians



HGVPU - Pole Tip Location from Girder Centerline

Nominal Gap :	9.000	US Full :	9.0002	DS Full :	9.0004
Nom. Taper :	0.000	US Wall Half :	4.4960	DS Wall Half :	4.5022
		US Aisle Half :	4.4987	DS Aisle Half :	4.5013

S/N	: HXU_026
Date	: 23-SEP-2019
Data Set	: 0001
Run	: FINAL
Cam Pos.	: B

Values Calculated from Regression Line End Points

Dimension	X Value	Y Value	Z Value	Calc. Value
US Aisle Pole Tip(1)	4.483	0.000	8.750	
US Wall Pole Tip(1)	-4.517	0.000	8.750	
US Sym. Pt.	-0.017			
US Gap				9.000
DS Aisle Pole Tip(260)	4.515	0.000	3375.750	
DS Wall Pole Tip(260)	-4.485	0.000	3375.750	
DS Sym. Pt.	0.015			
DS Gap				9.000
Taper				0.000


Dimensions in MM



HGVPU - Gap Calc. from Regression Line End Points

Nominal Gap :	9.000	US Full :	9.0002	DS Full :	9.0004
Nom. Taper :	0.000	US Wall Half :	4.4960	DS Wall Half :	4.5022
		US Aisle Half :	4.4987	DS Aisle Half :	4.5013

S/N	: HXU_026
Date	: 23-SEP-2019
Data Set	: 0001
Run	: FINAL
Cam Pos.	: B




Pole Tip Gap at Nom. Beam Height

Blue = Pole Tip points
 Green = Mean line
 Red = Regression line thru points

Pole Tip Num. ----->

Pole Tip Symmetry Point at Nom. Beam Height



Girder centerline in reference to Pointed Magnets


Dimensions in MM, Angles in Milliradians



HGVPU - Pole Tip Gap and Symmetry Point Location

Nominal Gap :	9.000	US Full :	9.0002	DS Full :	9.0004
Nom. Taper :	0.000	US Wall Half :	4.4960	DS Wall Half :	4.5022
		US Aisle Half :	4.4987	DS Aisle Half :	4.5013


S/N	: HXU_026
Date	: 23-SEP-2019
Data Set	: 0001
Run	: FINAL
Cam Pos.	: B



Aisle Pole Tips

Pole Tip Num. ----->

Wall Pole Tips



Pole Tip Deviations from Jaw Mean Lines when aligned to actual Gap Sym. Plane

Dimensions in MM



HGVPU - Pole Tip Deviation from Mean Line

Nominal Gap :	9.000	US Full :	9.0002	DS Full :	9.0004
Nom. Taper :	0.000	US Wall Half :	4.4960	DS Wall Half :	4.5022
		US Aisle Half :	4.4987	DS Aisle Half :	4.5013

S/N	: HXU_026
Date	: 23-SEP-2019
Data Set	: 0001
Run	: FINAL
Cam Pos.	: B