Top Jaw Pole Tips

Mean TOP = 10.0519   Regression Line Ang. (mrad) = 0.0096

Pole Tip Num. ---->

Bottom Jaw Pole Tips

Minimum Effective Gap = 20.013

Mean BTM = -10.0343   Regression Line Ang. (mrad) = 0.0200

Y Value Scales Centered on Mean Values
Step Between Measured Pole Tips = 7

Regression Line Through Points = - - - -
Dimensions in mm

SLAC
NATIONAL ACCELERATOR LABORATORY
METROLOGY

LCLS II - SXR Undulator
Nominal Gap = 20   Nominal Taper = 0.000
Gap Reading = 20.0000   US Encoder = 20.0000   DS Encoder = 20.0000

04-APR-2019
S/N = 002
D/S = 0001
Run = 10

Gap Between Opposing Pole Tips

20.036	
20.032	
20.028	
20.024	
20.02	
20.016	
20.012	
20.008	
20.004	

4 8 12 16 20 24 28 32 36 40 44 48 52 56 60 64 68 72 76 80 84 88 92 96 100 104 108 112 116 120 124 128 132 136 140 144 148 152 156 160 164 168 172

19.996	
19.992	
19.988	
19.984	
19.98	
19.976	
19.972	
19.968	
19.964	

Mean Gap =   20.0862

Step Between Measured Pole Tips =   7

Dimensions in mm

SLAC
NATIONAL ACCELERATOR LABORATORY
METROLOGY

LCLS II - SXR Undulator
Nominal Gap = 20   Nominal Taper = 0.000
Gap Reading = 20.0000   US Encoder = 20.0000   DS Encoder = 20.0000

04-APR-2019
S/N =   002
D/S=   0001
Run=   10

Symmetry Point Between Pole Tips

Mean Symmetry Value =   0.0088

Step Between Measured Pole Tips =   7

Dimensions in mm

LCLS II - SXR Undulator

Nominal Gap = 20   Nominal Taper = 0.000

Gap Reading = 20.0000   US Encoder = 20.0000   DS Encoder = 20.0000

SLAC
NATIONAL ACCELERATOR LABORATORY
METROLOGY

04-APR-2019
S/N =   002
D/S=   0001
Run=   10

Top and Bottom Jaw
Regression Line Intersect Points

Jaw	First Pole (Pole 1)	US Actuator (Pole 39)	DS Actuator (Pole 135)	Last Pole (Pole 174)
Top	10.0361	10.0432	10.0613	10.0686
Bottom	-10.0675	-10.0526	-10.0152	-9.9999
Gap	20.1036			20.0685
Taper				-0.0351

Summary of Mean Values

Top Jaw Poles	Btm. Jaw Poles	Gap Values	Sym. Pt. Values
10.0519	-10.0343	20.0862	0.0088

Additional Calculated Values

Bottom Pole #1 Z Value	980.303
Top Jaw Pitch (mrad)	0.010
Bottom Jaw Pitch(mrad)	0.020
Minimum Effective Gap	20.013
Reference Block Gap	6.810

Dimensions in mm

SLAC
NATIONAL ACCELERATOR LABORATORY
METROLOGY

LCLS II - SXR Undulator
Nominal Gap = 20   Nominal Taper = 0.000
Gap Reading = 20.0000   US Encoder = 20.0000   DS Encoder = 20.0000

04-APR-2019
S/N = 002
D/S= 0001
Run= 10