


Y Value Scales Centered on Mean Values
 Step Between Measured Pole Tips = 5

Regression Line Through Points = -----
 Dimensions in mm

	<h2 style="margin: 0;">LCLS II - SXR Undulator</h2> <p style="margin: 0;">Nominal Gap = 20</p> <p style="margin: 0;">Gap Reading = 20.0000 US Encoder = 20.0000 DS Encoder = 20.0000</p>	<p style="margin: 0;">05-FEB-2018</p> <p style="margin: 0;">S/N = 005</p> <p style="margin: 0;">D/S = 0001</p> <p style="margin: 0;">Run = 06</p>
---	--	---

Gap Between Opposing Pole Tips



Step Between Measured Pole Tips = 5

Dimensions in mm



LCLS II - SXR Undulator

Nominal Gap = 20

Gap Reading = 20.0000 US Encoder = 20.0000 DS Encoder = 20.0000


05-FEB-2018

S/N = 005

D/S = 0001

Run = 06

Symmetry Point Between Pole Tips



Mean Symmetry Value = 0.2372

Step Between Measured Pole Tips = 5

Dimensions in mm



LCLS II - SXR Undulator

Nominal Gap = 20

Gap Reading = 20.0000 US Encoder = 20.0000 DS Encoder = 20.0000

05-FEB-2018

S/N = 005

D/S = 0001

Run = 06

Top and Bottom Jaw Regression Line Intersect Points

Jaw	First Pole (Pole 1)	US Actuator (Pole 39)	DS Actuator (Pole 135)	Last Pole (Pole 174)
Top	10.2275	10.2342	10.2510	10.2579
Bottom	-9.7836	-9.7766	-9.7588	-9.7516

Summary of Mean Values

Top Jaw Poles	Btm. Jaw Poles	Gap Values	Sym. Pt. Values
10.2424	-9.7680	20.0103	0.2372

Additional Calculated Values

Bottom Pole #1 Z Value	979.331
Top Jaw Pitch (mrad)	0.009
Bottom Jaw Pitch(mrad)	0.009
Minimum Effective Gap	19.973
Reference Block Gap	6.808

Dimensions in mm



LCLS II - SXR Undulator

Nominal Gap = 20

Gap Reading = 20.0000 US Encoder = 20.0000 DS Encoder = 20.0000

05-FEB-2018

S/N = 005

D/S= 0001

Run= 06