SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 02−07−2012
Time: 11:10:59

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−18
DATASET Number: 4
Tuning Stage: Fine Tuning
Run Number: 2
Measurement Type: Z Scans
Operator: YL
Comment: find Y at min K
Session first run: 2
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−18\DATASET0004\Fine Tuning\Z Scans\Run 002\bscanz.dat

Temperature (C)
L143−112000−18:−−> T1 19.96 −−> T2 19.94 −−> T5 19.93 −−> T3 19.95 −−> Air 19.97 −−> T4 19.94

Axes position (m) X:0.029326 Y:0.000311
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000959 V
Vy_0i = −0.003559 V


Bx vs Z
x 10^-3
10
8
6
4
2
0
−2
−4
−6
−8
13
46
80
113
146
180
213
Pole
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
3
2
1
0
−1
−2
−3
−4
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-5
13
46
80
113
146
180
213
Pole
Y (m)
Z position (m)
1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5



Phase Error: Ave = 0.000000 deg, RMS = 16.032223 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
50
0
−50
−100
−150
−200
−250
−300
−350
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)