

BL9 Be Window

10-7-03
MP JM

Y

<u>F</u>	<u>G</u>	<u>H</u>	<u>I</u>	Stopper B (check)	
18.191	18.191	18.191	18.191	18.191	HL9N05
<u>6.970</u>	<u>-0.131</u>	<u>8.050</u>	<u>3.182</u>	<u>-1.011</u>	-41.115
11.221	18.322	10.141	15.009	19.202	40.750
,	,	,	,	,	<u>18.556</u>
10.221	17.322	9.141	14.009	18.202	18.191
10.230	17.288		13.970		
10.252	17.328		14.010		
10.221	17.322		14.007		

BeW

<u>A</u>	<u>B</u>
18.191	18.191
<u>3.016</u>	<u>3.032</u>
15.175	15.159
,	,
14.175	14.159
14.185	14.178
14.190	14.179

X

Buck in
 For V 40.053 @ sm08W3
 Near V 44.861 @ sm08W9
 1 F (-) 13.000 + 1.75
 1 N (-) 13.415 + 1.75
 2 F (-) 8.400 + 1.75
 2 N (-) 12.385 + 1.75
 S/R F 9.090 - 1.75 = 7.340
 S/R N 13.898 - 1.75 = 12.148
 LOS 30.963
 check 41.522 @ sm08W6

D

18.191
<u>7.944</u>
10.247
,
9.247
9.268 -21

ck stopper	GrF		BeW		Stopper
<u>B</u>	<u>B</u>	<u>D</u>	<u>F</u>	<u>G</u>	<u>A</u>
30.963	30.963	30.963	30.963	30.963	30.963
<u>12.518</u>	<u>8.381</u>	<u>4.017</u>	<u>4.114</u>	<u>8.092</u>	<u>6.879</u>
18.445	22.582	30.946	30.849	22.865	24.084
<u>1</u>	<u>13</u>	<u>13</u>	<u>13</u>	<u>13</u>	<u>13</u>
17.445	9.582	17.946	17.849	9.865	11.084
17.428	9.572	17.912	17.845	9.868	11.092
17.448				9.799	