



Jobs Safety Analysis (JSA)

Date 2/23/2010

JOB/ACTIVITY NAME: Take as-built measurements of the shaft at sect 19		JSA #:
DEPARTMENT/GROUP NAME MET / AEG	BLDG/AREA LOCATION(s): Linac Sect 19	OTHER INFORMATION:
REQUIRED PERSONAL PROTECTIVE EQUIPMENT FOR ENTIRE JOB <input checked="" type="checkbox"/> safety glasses <input checked="" type="checkbox"/> safety shoes <input type="checkbox"/> chemical resistant gloves <input checked="" type="checkbox"/> other reflective vest <input checked="" type="checkbox"/> other flashlight <input type="checkbox"/> chemical goggles <input checked="" type="checkbox"/> hard hat <input type="checkbox"/> welding gloves <input type="checkbox"/> face shield <input type="checkbox"/> harness lanyard <input type="checkbox"/> gloves when adjusting component <input checked="" type="checkbox"/> other long pants / sleeves <input type="checkbox"/> other _____ <input type="checkbox"/> welding goggles <input type="checkbox"/> hearing protection PPE only required in the linac tunnel, safety vest required on street		

Basic Steps	Potential Hazards	Controls
<u>Set Up Equipment and Targeting</u> <ul style="list-style-type: none"> ▪ Set up survey instruments (includes Class 2 or 3R laser instruments) ▪ Place targets on and around shaft ▪ Plug in instruments ▪ Use illumination if necessary 	<ul style="list-style-type: none"> ▪ Radiation ▪ Electrocutation 	<ul style="list-style-type: none"> ▪ Follow posted radiation signs and read AHA ▪ Inspect hand or power tools and cords before use ▪ Inspect power cords for any defects and use GFCIs (never daisy chain cords)
<u>Perform Survey</u> <ul style="list-style-type: none"> ▪ Place area warning signs for laser BUT ONLY WHEN IN USE ▪ Make measurements ▪ Remove any laser warning signs when not in use 	<ul style="list-style-type: none"> ▪ Prolonged eye exposure to laser 	<ul style="list-style-type: none"> ▪ Inspect ladders before use and never climb to the top rungs ▪ No unattended operation of laser instruments ▪ Use warning signs when laser instruments are in use (laser scanner requires “DANGER” sign) ▪ Must verify that laser scanner range interlock of 0.3 meters is active at start of operation and monitor proper scanning during measurement

JOB TITLE: Take as-built measurements of the shaft at sect 19

DATE: 2/23/2010

I understand & will adhere to the steps, hazards & controls as described in this JSA. I understand that performing steps out of sequence may pose hazards that have not been evaluated, nor authorized. I will contact my supervisor prior to continuing work, if the scope of work changes or new hazards are introduced.

I understand I have the authority and responsibility to stop work I believe to be unsafe.

Worker Name (please print)

Signature

Date

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

I have reviewed the steps, hazards & controls described in this JSA with all workers listed above and authorize them to perform the work. Workers are qualified (i.e. licensed or certified, as required & in full compliance with SLAC training requirements) to perform this activity.

Georg Gassner

Supervisor

Signature

Date

I have communicated area hazards with the supervisor or listed worker(s) for this activity and have coordinated the described activity with affected occupants. The above listed workers are released to perform described scope of work in the following area(s): _____

7:30 kick off meeting

Area or Building Manager

Signature

Date