SLAC Magnetic Measurements

EPU Analysis

Parameters:
INPUT-FILE-DIR =V:\MET\MagServe\MagData\DELTA\Delta Data 2015\New Measurements\Run 142 Repeat 2014 Meas With New
INPUT-FILE-NAME =hall2-anal-probe1-field.dat
INPUT-FILE-TYPE =ZBXYZH
CORR-REQUIRED =0
GAMMA =26671.59
NOM-LAMBDA-U =0
NOM-K-VALUE =0
NOM-LAMBDA-R =0
NUM-POLES =196
NUM-END-POLES =4
CELL-LENGTH =3.656


Bx, By, Bz vs Zm
Bx (T)
By (T)
Bz (T)
Zm Measurement Position (m)
0.4
0.2
0
-0.2
-0.4
2
1
-1
-2
0
0.5
1
1.5
2
2.5
3
3.5
4


Bx and By vs Z
Pole
5
36
67
98
130
161
192
Bx
By
0.4
0.3
0.2
0.1
0
-0.1
-0.2
-0.3
-0.4
Bx, By (T)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Bx vs Z With Fitted Peaks And Zeros
Bx (T)
Z (m)
Pole
6
37
68
99
131
162
193
0.4
0.3
0.2
0.1
0
-0.1
-0.2
-0.3
-0.4
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


By vs Z With Fitted Peaks And Zeros
By (T)
Z (m)
Pole
5
36
67
98
130
161
192
0.4
0.3
0.2
0.1
0
-0.1
-0.2
-0.3
-0.4
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Abs(Fitted Peak Bx) vs Z, Excluding Ends
6
37
68
99
131
162
193
Pole
0.39
0.385
0.38
0.375
0.37
0.365
0.36
0.355
0.35
Abs(Peak Bx) (T)
Peak Fields: Ave = 0.369350 T, RMS = 0.008258 T
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Abs(Fitted Peak By) vs Z, Excluding Ends
5
36
67
98
130
161
192
Pole
0.4
0.39
0.38
0.37
0.36
0.35
0.34
Abs(Peak By) (T)
Peak Fields: Ave = 0.372218 T, RMS = 0.008158 T
-1.5
-1
-0.5
0
0.5
1
1.5
Z (m)


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
Bx Peak And Zero Field Spacing (m)
0.017
0.0165
0.016
0.0155
0.015
6
37
68
99
131
162
193
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.016001 m, RMS = 0.000180 m
Zero Field Spacing: Ave = 0.016000 m, RMS = 0.000122 m
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


By Peak And Zero Field Spacing vs Z, Excluding Ends
By Peak And Zero Field Spacing (m)
0.0165
0.016
0.0155
5
36
67
98
130
161
192
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.015999 m, RMS = 0.000166 m
Zero Field Spacing: Ave = 0.015999 m, RMS = 0.000131 m
-1.5
-1
-0.5
0
0.5
1
1.5
Z (m)


Bx Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^{0}
10^{-1}
10^{-2}
10^{-3}
10^{-4}
10^{-5}
10^{-6}
0
2
4
6
8
10
12
14
16
18
20


By Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^0
10^-1
10^-2
10^-3
10^-4
10^-5
10^-6
10^-7
0
2
4
6
8
10
12
14
16
18
20


X Trajectory
10^-6
5
36
67
98
130
161
192
Pole
2
0
-2
-4
-6
-8
-10
-12
X Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory
10^-6
5
36
67
98
130
161
192
Pole
2
0
-2
-4
-6
-8
-10
-12
Y Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


X And Y Trajectories
10^-6
2
0
-2
-4
-6
-8
-10
-12
X, Y Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)
X
Y


XY Trajectory Projection
10^-6
2
0
-2
-4
-6
-8
-10
-12
Y Trajectory (m)
-12
-10
-8
-6
-4
-2
0
2
X Trajectory (m)
10^-6


X Trajectory, Slope Corrected
10^-6
3
2.5
2
1.5
1
0.5
0
X Trajectory, Corrected (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory, Slope Corrected
10^-6
4
3
2
1
0
-1
-2
Y Trajectory, Corrected (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Phase Relative To Cell Entrance
700
600
500
400
300
200
100
0
Phase (rad)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Phase Error At Field Peaks, No Ends
5
36
67
98
130
161
192
Pole
120
100
80
60
40
20
0
-20
-40
-60
-80
Phase Error (deg)
-1.5
-1
-0.5
0
0.5
1
1.5
Z (m)
Phase Error: Ave = 0.000000 deg, RMS = 47.257294 deg


Phase Error At Field Peaks, No Ends, Trajectory Slope Corrected
5
36
67
98
130
161
192
Pole
80
60
40
20
0
-20
-40
-60
Phase Error (deg)
Phase Error: Ave = 0.000000 deg, RMS = 28.262118 deg
-1.5
-1
-0.5
0
0.5
1
1.5
Z (m)


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
5
36
67
98
130
161
192
Pole
-1400
-1420
-1440
-1460
-1480
-1500
-1520
-1540
-1560
-1580
Phase Error (deg)
-1.5
-1
-0.5
0
0.5
1
1.5
Z (m)


Phase Integral And Effective Length
10^-5
1.2
1
0.8
0.6
0.4
0.2
0
PI
Fit
Phase Integral (T^2m^3)
Effective Length = 3.081500 m
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Re and Im Parts Of Ex(!), Forward Direction, ! = !1
90
1.5e-11
120
60
1e-11
150
30
5e-12
180
0
210
330
240
300
270


Re and Im Parts Of Ey(!), Forward Direction, ! = !1
90
1.5e-11
120
60
1e-11
150
30
5e-12
180
0
210
330
240
300
270


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
10^{18}
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
5
4.5
4
3.5
3
2.5
2
1.5
1
0.5
0
0
5
10
15
! / !$_1$


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
10^{18}
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
12
10
8
6
4
2
0
0.96
0.97
0.98
0.99
1
1.01
1.02
1.03
1.04
1.05
! / !$_1$


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
10^{18}
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
12
10
8
6
4
2
0
2.96
2.97
2.98
2.99
3
3.01
3.02
3.03
3.04
3.05
! / !$_1$


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
10^{18}
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
0
1
2
3
4
5
6
7
8
4.96
4.97
4.98
4.99
5
5.01
5.02
5.03
5.04
5.05
! / !$_1$