SLAC Magnetic Measurements

EPU Analysis

Parameters:
INPUT-FILE-DIR =V:\MET\MagServe\MagData\DELTA\Delta Data 2015\Repeat 2014 Measurements\Data Set 1 Run 042\CPRMF\
INPUT-FILE-NAME =hall2-anal-probe1-field.dat
INPUT-FILE-TYPE =ZBXYZH
CORR-REQUIRED =0
GAMMA =26671.59
NOM-LAMBDA-U =0
NOM-K-VALUE =0
NOM-LAMBDA-R =0
NUM-POLES =196
NUM-END-POLES =4
CELL-LENGTH =3.656


Bx, By, Bz vs Zm
Bx (T)
0.2
0.1
0
-0.1
-0.2
-0.3
By (T)
0.4
0.2
0
-0.2
-0.4
Bz (T)
1
0.5
0
-0.5
-1
-3.5
-3
-2.5
-2
-1.5
-1
-0.5
0
Zm Measurement Position (m)


Bx and By vs Z
4
35
66
98
129
160
192
Pole
Bx
By
0.3
0.2
0.1
0
-0.1
-0.2
-0.3
Bx, By (T)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Bx vs Z With Fitted Peaks And Zeros
5
35
62
93
120
149
175
Pole
0.2
0.1
0
-0.1
-0.2
-0.3
-0.4
Bx (T)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


By vs Z With Fitted Peaks And Zeros
4
35
66
98
129
160
192
Pole
0.4
0.3
0.2
0.1
0
-0.1
-0.2
-0.3
-0.4
By (T)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Abs(Fitted Peak Bx) vs Z, Excluding Ends
5
35
62
93
120
149
175
Pole
Abs(Peak Bx) (T)
0.06
0.05
0.04
0.03
0.02
0.01
0
Peak Fields: Ave = 0.015711 T, RMS = 0.007509 T
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Abs(Fitted Peak By) vs Z, Excluding Ends
4
35
66
98
129
160
192
Pole
Abs(Peak By) (T)
0.08
0.07
0.06
0.05
0.04
0.03
0.02
0.01
0
Peak Fields: Ave = 0.028873 T, RMS = 0.009439 T
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
Bx Peak And Zero Field Spacing (m)
Z (m)
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.017659 m, RMS = 0.009683 m
Zero Field Spacing: Ave = 0.017684 m, RMS = 0.009010 m


By Peak And Zero Field Spacing vs Z, Excluding Ends
By Peak And Zero Field Spacing (m)
Z (m)
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.015991 m, RMS = 0.003369 m
Zero Field Spacing: Ave = 0.016007 m, RMS = 0.001958 m


Bx Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^-3
10^-4
10^-5
10^-6
10^-7
0
2
4
6
8
10
12
14
16
18
20


By Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^-2
10^-3
10^-4
10^-5
10^-6
10^-7
0
2
4
6
8
10
12
14
16
18
20


X Trajectory
×10-6
2
0
-2
-4
-6
-8
-10
4
35
66
98
129
160
192
Pole
X Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory
×10-6
14
12
10
8
6
4
2
0
-2
4
35
66
98
129
160
192
Pole
Y Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


X And Y Trajectories
×10-5
1.5
1
0.5
0
-0.5
-1
X, Y Trajectory (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)
X
Y


XY Trajectory Projection
×10-6
14
12
10
8
6
4
2
0
-2
Y Trajectory (m)
-10
-8
-6
-4
-2
0
2
X Trajectory (m)
×10-6


X Trajectory, Slope Corrected
×10-6
2.5
2
1.5
1
0.5
0
-0.5
X Trajectory, Corrected (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory, Slope Corrected
×10-6
0
-0.5
-1
-1.5
-2
-2.5
-3
Y Trajectory, Corrected (m)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Phase Relative To Cell Entrance
700
600
500
400
300
200
100
0
Phase (rad)
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Phase Error At Field Peaks, No Ends
4
35
66
98
129
160
192
Pole
120
100
80
60
40
20
0
-20
-40
-60
Phase Error (deg)
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)
Phase Error: Ave = 0.000000 deg, RMS = 46.559577 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
4
35
66
98
129
160
192
Pole
400
200
0
-200
-400
-600
-800
-1000
-1200
-1400
Phase Error (deg)
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z (m)


Phase Integral And Effective Length
×10^-7
PI
Fit
Phase Integral (T^2m^3)
Z (m)
Effective Length = 3.078030 m
4
3.5
3
2.5
2
1.5
1
0.5
0
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Re and Im Parts Of Ex(ω), Forward Direction, ω = ω1
90
3e-12
120
60
2e-12
150
30
1e-12
180
0
210
330
240
300
270


Re and Im Parts Of Ey(ω), Forward Direction, ω = ω1
90
1.5e-12
120
60
1e-12
150
30
5e-13
180
0
210
330
240
300
270


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
$\times 10^{15}$
5
4.5
4
3.5
3
2.5
2
1.5
1
0.5
0
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
0
5
10
15
ω / ω_1


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
$\times 10^{17}$
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
3
2.5
2
1.5
1
0.5
0
0.96
0.97
0.98
0.99
1
1.01
1.02
1.03
1.04
1.05
ω / ω_1


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
$\times 10^{16}$
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
3
2.5
2
1.5
1
0.5
0
2.96
2.97
2.98
2.99
3
3.01
3.02
3.03
3.04
3.05
ω / ω_1


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
$\times 10^{16}$
3.5
3
2.5
2
1.5
1
0.5
0
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
Measured
Ideal
4.96
4.97
4.98
4.99
5
5.01
5.02
5.03
5.04
5.05
ω / ω_1