SLAC Magnetic Measurements

EPU Analysis
––––––––––––

Parameters:
INPUT–FILE–DIR =V:\MET\MagServe\MagData\DELTA\Superpose Quadrants Q1 300microns\LPHMF\KR040(
INPUT–FILE–NAME =superpose–quadrants.dat
INPUT–FILE–TYPE =ZBXYZH
CORR–REQUIRED =0
GAMMA =26671.59
NOM–LAMBDA–U =0
NOM–K–VALUE =0
NOM–LAMBDA–R =0
NUM–POLES =196
NUM–END–POLES =4
CELL–LENGTH =3.656


Bx, By, Bz vs Zm
Bx (T)
0.5
0
−0.5
By (T)
0.2
0.1
0
−0.1
−0.2
Bz (T)
1
0.5
0
−0.5
−1
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Zm Measurement Position (m)


Bx and By vs Z
6
37
66
97
129
158
189
Pole
Bx
By
0.5
0.4
0.3
0.2
0.1
0
−0.1
−0.2
−0.3
−0.4
−0.5
Bx, By (T)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Bx vs Z With Fitted Peaks And Zeros
5
36
68
99
130
161
193
Pole
0.5
0
−0.5
Bx (T)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


By vs Z With Fitted Peaks And Zeros
6
37
66
97
129
158
189
Pole
0.2
0.15
0.1
0.05
0
−0.05
−0.1
−0.15
−0.2
By (T)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Abs(Fitted Peak Bx) vs Z, Excluding Ends
Abs(Peak Bx) (T)
Z (m)
Pole
5
36
68
99
130
161
193
Peak Fields: Ave = 0.426493 T, RMS = 0.007665 T


Abs(Fitted Peak By) vs Z, Excluding Ends
Abs(Peak By) (T)
Z (m)
Pole
6
37
66
97
129
158
189
Peak Fields: Ave = 0.022396 T, RMS = 0.006064 T


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
Bx Peak And Zero Field Spacing (m)
Z (m)
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.016007 m, RMS = 0.000761 m
Zero Field Spacing: Ave = 0.016000 m, RMS = 0.000107 m


By Peak And Zero Field Spacing vs Z, Excluding Ends
By Peak And Zero Field Spacing (m)
Z (m)
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.016334 m, RMS = 0.004722 m
Zero Field Spacing: Ave = 0.016349 m, RMS = 0.004205 m


Bx Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^{0}
10^{-1}
10^{-2}
10^{-3}
10^{-4}
10^{-5}
10^{-6}
0
2
4
6
8
10
12
14
16
18
20


By Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^{-1}
10^{-2}
10^{-3}
10^{-4}
10^{-5}
10^{-6}
10^{-7}
10^{-8}
0
2
4
6
8
10
12
14
16
18
20


X Trajectory
x 10^-6
5
36
68
99
130
161
193
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X Trajectory (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory
x 10^-6
5
36
68
99
130
161
193
Pole
2.5
2
1.5
1
0.5
0
−0.5
Y Trajectory (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


X And Y Trajectories
x 10^-6
2.5
2
1.5
1
0.5
0
−0.5
−1
X, Y Trajectory (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)
X
Y


XY Trajectory Projection
x 10^-6
2.5
2
1.5
1
0.5
0
−0.5
Y Trajectory (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
X Trajectory (m)
x 10^-6


X Trajectory, Slope Corrected
x 10^-6
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X Trajectory, Corrected (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Y Trajectory, Slope Corrected
x 10^-6
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y Trajectory, Corrected (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Phase Relative To Cell Entrance
Phase (rad)
700
600
500
400
300
200
100
0
−100
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Phase Error At Field Peaks, No Ends
5
36
68
99
130
161
193
Pole
70
60
50
40
30
20
10
0
−10
−20
−30
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)
Phase Error: Ave = −0.000000 deg, RMS = 17.840998 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
5
36
68
99
130
161
193
Pole
−1150
−1160
−1170
−1180
−1190
−1200
−1210
−1220
−1230
−1240
−1250
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z (m)


Phase Integral And Effective Length
x 10^-6
PI
Fit
Phase Integral (T^2m^3)
Z (m)
Effective Length = 3.079800 m
9
8
7
6
5
4
3
2
1
0
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2


Re and Im Parts Of Ex(ω), Forward Direction, ω = ω1
90
1.5e−12
120
60
1e−12
150
30
5e−13
180
0
210
330
240
300
270


Re and Im Parts Of Ey(ω), Forward Direction, ω = ω1
90
2e−11
120
60
1.5e−11
150
30
1e−11
5e−12
180
0
210
330
240
300
270


Angular Number Spectrum, (ph/sec/mrad2/0.1%bw/0.1A), Forward Direction
x 10^18
12
10
8
6
4
2
0
Angular Number Spectrum (ph/sec/mrad2/0.1%bw/0.1A)
0
5
10
15
ω / ω1


Angular Number Spectrum, (ph/sec/mrad2/0.1%bw/0.1A), Forward Direction
x 10^18
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad2/0.1%bw/0.1A)
ω / ω1
0
2
4
6
8
10
12
0.96
0.97
0.98
0.99
1
1.01
1.02
1.03
1.04
1.05


Angular Number Spectrum, (ph/sec/mrad2/0.1%bw/0.1A), Forward Direction
x 10^18
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad2/0.1%bw/0.1A)
ω / ω1
0
1
2
3
4
5
6
7
8
9
10
2.96
2.97
2.98
2.99
3
3.01
3.02
3.03
3.04
3.05


Angular Number Spectrum, (ph/sec/mrad2/0.1%bw/0.1A), Forward Direction
x 10^18
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad2/0.1%bw/0.1A)
ω / ω1
5
4.5
4
3.5
3
2.5
2
1.5
1
0.5
0
4.96
4.97
4.98
4.99
5
5.01
5.02
5.03
5.04
5.05