SLAC Magnetic Measurements
Hall Probe Calibration

Header:
SLAC Magnetic Measurements
Date: 06-15-2021
Time: 11:41:50

Project: LCLS-II
Device Type: Hall probe
Data Type: Y
Serial Number: SENIS-27-14
Run Number: 3
Measurement Type: HPCS
Operator: YL
Comment: PC71027; +6.00002, -6.00002, +0.99999

Current(A) T(C) Case T(C) Est.Field(T) Voltage Field

Parameters:
INPUT-FILE-DIR =T:\MagData\LCLS-II\Hall probe\SENIS-27-14\HPCS-003\
INPUT-FILE-NAME =hpcs-dat.001
POLY-FIT-ORDER =15
NUM-SIG-OUTLIER =2
NOM-CALIB-CONST =0.2
MAX-B-NMR-FIT =1.65


Hall Probe Temperature
Thall (C)
Bnmr (T)
20.26
20.24
20.22
20.2
20.18
20.16
20.14
20.12
20.1
20.08
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Reference Hall Probe
Bref - Bnmr (T)
Bnmr (T)
0.5
0
-0.5
-1
-1.5
-2
-2.5
-3
-3.5
-4
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Vhall vs Bnmr, Hall Probe Offset Voltage
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
10
8
6
4
2
0
-2
-4
-6
-8
-10
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Fit Bnmr vs Vhall Offset Corrected
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1


Polynomial Fit Residuals
Bnmr - Bfit (T)
Offset Corrected Hall Probe Voltage (V)
0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1


Vhall vs Bnmr, Hall Probe Offset Voltage, No Outliers
Measurements
Fit
Hall Probe Voltage (V)
Bnmr (T)
1
0.8
0.6
0.4
0.2
0
-0.2
-0.4
-0.6
-0.8
-1
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Fit Bnmr vs Vhall Offset Corrected, No Outliers
Measurements
Bnmr (T)
1
0.8
0.6
0.4
0.2
0
-0.2
-0.4
-0.6
-0.8
-1
-10
-8
-6
-4
-2
0
2
4
6
8
10
Offset Corrected Hall Probe Voltage (V)


Polynomial Fit Residuals, No Outliers
Bnmr - Bfit (T)
Offset Corrected Hall Probe Voltage (V)
0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1


(Calibrated Field - Nominal Hall Field) vs Offset Corrected Hall Voltage, No Outliers
Bhallcalib - Bhallnom (T)
Offset Corrected Hall Probe Voltage (V)
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-10
-8
-6
-4
-2
0
2
4
6
8
10