SLAC Magnetic Measurements

Planar Insertion Device Analysis

Parameters:
INPUT-FILE-DIR =S:\MagData\LCLS2\Undulator\HGVPU\DATASET0001\Fine Tuning\Z Scans\Run 086\
INPUT-FILE-NAME =x+00000-y+000-bscanz.dat
INPUT-FILE-TYPE =ZVXYBXYH
CORR-REQUIRED =1
GAMMA =26689
NOM-LAMBDA-U =0.026
NOM-K-VALUE =3.5
NOM-LAMBDA-R =1.3004e-10
NUM-POLES =260
NUM-END-POLES =6
CELL-LENGTH =3.656


Bx Field Correction vs Zm
10^-5
-1.9999999999998
-1.99999999999985
-1.9999999999999
-1.99999999999995
-2
-2.00000000000005
-2.0000000000001
-2.00000000000015
-2.0000000000002
Bx Corr (T)
0
0.5
1
1.5
2
2.5
3
3.5
4
4.5


By Field Correction vs Zm
10^-5
-8.599999999998
-8.599999999999
-8.6
-8.600000000001
-8.600000000002
-8.600000000003
By Corr (T)
0
0.5
1
1.5
2
2.5
3
3.5
4
4.5
Zm Measurement Position (m)


Bx, By vs Zm
10^-3
Bx (T)
By (T)
Zm Measurement Position (m)


Bx vs Z With Fitted Peaks And Zeros
10^-3
Bx (T)
Z (m)


By vs Z With Fitted Peaks And Zeros
15
54
92
130
169
207
246
Pole
By (T)
Z (m)


Abs(Fitted Peak Bx) vs Z, Excluding Ends
Abs(Peak Bx) (T)
Z (m)
Peak Fields: Ave = 0.000000 T, RMS = 0.000000 T
1
0.5
0
-0.5
-1
-1
-0.8
-0.6
-0.4
-0.2
0
0.2
0.4
0.6
0.8
1


Abs(Fitted Peak By) vs Z, Excluding Ends
Abs(Peak By) (T)
Z (m)
Peak Fields: Ave = 0.936731 T, RMS = 0.002940 T
15
54
92
130
169
207
246
Pole
0.95
0.945
0.94
0.935
0.93
0.925
0.92
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
Bx Peak And Zero Field Spacing (m)
Z (m)
Peaks
Zeros
Peak Field Spacing: Ave = 0.000000 m, RMS = 0.000000 m
Zero Field Spacing: Ave = 0.000000 m, RMS = 0.000000 m


By Peak And Zero Field Spacing vs Z, Excluding Ends
By Peak And Zero Field Spacing (m)
Z (m)
15
54
92
130
169
207
246
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.012999 m, RMS = 0.000020 m
Zero Field Spacing: Ave = 0.012999 m, RMS = 0.000030 m


s s Bx dz dz and s s By dz dz
10^-5
I2x
I2x Filt
I2y
I2y Filt
s s B dz dz (Tm**2)
Z (m)
4
2
0
-2
-4
-6
-8
-10
-12
-14
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5


X Trajectory
10^-6
15
53
92
130
168
207
245
Pole
1
0.5
0
-0.5
-1
-1.5
-2
-2.5
-3
X (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
10^-6
15
53
92
130
168
207
245
Pole
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
Y (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


X Trajectory, Slope Corrected
10^-6
15
53
92
130
168
207
245
Pole
0.5
0
-0.5
-1
-1.5
-2
-2.5
-3
X Trajectory, Corrected (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory, Slope Corrected
10^-7
3
2.5
2
1.5
1
0.5
0
-0.5
15
53
92
130
168
207
245
Pole
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Y Trajectory, Corrected (m)
Z position (m)


Phase Relative To Cell Entrance
900
800
700
600
500
400
300
200
100
0
-100
Phase (rad)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z (m)



Phase Error: Ave = -0.000000 deg, RMS = 5.255928 deg

Phase Match Error: Ave = 562.950373 deg, RMS = 5.327971 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
10^4
0
-0.5
-1
-1.5
-2
-2.5
Phase Error (deg)
15
53
92
130
168
207
245
Pole
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
Z position (m)