SLAC Magnetic Measurements

Planar Insertion Device Analysis

Parameters:
INPUT-FILE-DIR =S:\MagData\LCLS-II\Undulator\SXR-REFERENCE\DATASET0001\Tuning\Z Scans\Run 004\
INPUT-FILE-NAME =x+00000-y+000-bscanz.dat
INPUT-FILE-TYPE =ZVXYBXYH
CORR-REQUIRED =0
GAMMA =26689
NOM-LAMBDA-U =0.03
NOM-K-VALUE =3.5
NOM-LAMBDA-R =1.5004e-10
NUM-POLES =226
NUM-END-POLES =4
CELL-LENGTH =3.656


Bx, By vs Zm
10^-3
Bx (T)
By (T)
Zm Measurement Position (m)


Bx vs Z With Fitted Peaks And Zeros
10^-3
Bx (T)
Z (m)


By vs Z With Fitted Peaks And Zeros
13
47
80
113
147
180
214
Pole
By (T)
Z (m)


Abs(Fitted Peak Bx) vs Z, Excluding Ends
Abs(Peak Bx) (T)
Z (m)
Peak Fields: Ave = 0.000000 T, RMS = 0.000000 T


Abs(Fitted Peak By) vs Z, Excluding Ends
13
47
80
113
147
180
214
Pole
Abs(Peak By) (T)
Z (m)
Peak Fields: Ave = 1.205271 T, RMS = 0.006463 T


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
Bx Peak And Zero Field Spacing (m)
Z (m)
Peaks
Zeros
Peak Field Spacing: Ave = 0.000000 m, RMS = 0.000000 m
Zero Field Spacing: Ave = 0.000000 m, RMS = 0.000000 m


By Peak And Zero Field Spacing vs Z, Excluding Ends
By Peak And Zero Field Spacing (m)
Z (m)
13
47
80
113
147
180
214
Pole
Peaks
Zeros
Peak Field Spacing: Ave = 0.014999 m, RMS = 0.000043 m
Zero Field Spacing: Ave = 0.015000 m, RMS = 0.000047 m


s s Bx dz dz and s s By dz dz
10^-5
I2x
I2x Filt
I2y
I2y Filt
s s B dz dz (Tm**2)
Z (m)
4
2
0
-2
-4
-6
-8
-10
-12
-14
-16
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5


X Trajectory
10^-6
13
46
80
113
146
180
213
Pole
1
0.5
0
-0.5
-1
-1.5
-2
-2.5
-3
-3.5
X (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
Y (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


X Trajectory, Slope Corrected
10-6
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-2.5
-3
X Trajectory, Corrected (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory, Slope Corrected
10^-7
6
5
4
3
2
1
0
-1
13
46
80
113
146
180
213
Pole
Y Trajectory, Corrected (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Slippage
10^-8
Slippage
Fit
1.8
1.6
1.4
1.2
1
0.8
0.6
0.4
0.2
0
Slippage (m)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z (m)


Phase Relative To Cell Entrance
800
700
600
500
400
300
200
100
0
-100
Phase (rad)
-2.5
-2
-1.5
-1
-0.5
0
0.5
1
1.5
2
2.5
Z (m)



Phase Error: Ave = 0.000000 deg, RMS = 4.985393 deg



Phase Match Error: Ave = 555.487715 deg, RMS = 5.074536 deg