SLAC Magnetic Measurements
Hall Probe Calibration

Header:
SLAC Magnetic Measurements
Date: 06-24-2015
Time: 08:02:56

Project: LCLS
Device Type: Hall probe
Data Type: Y
Serial Number: SENIS-119-12
Run Number: 93
Measurement Type: HPCS
Operator: YL
Comment: Probe Y; calibration with voltmeter PC71027

Current(A) T(C) Est. Field(T) Voltage Field

Parameters:
INPUT-FILE-DIR =S:\MagData\LCLS\Hall probe\SENIS-119-12\HPCS-093\
INPUT-FILE-NAME =hpcs-dat.001
POLY-FIT-ORDER =13
NUM-SIG-OUTLIER =2
NOM-CALIB-CONST =0.2
MAX-B-NMR-FIT =1.5


Vhall vs Bnmr, Hall Probe Offset Voltage
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals
10^-5
8
6
4
2
0
-2
-4
-6
-8
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


Vhall vs Bnmr, Hall Probe Offset Voltage, No Outliers
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected, No Outliers
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals, No Outliers
10-5
6
4
2
0
-2
-4
-6
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


(Calibrated Field - Nominal Hall Field) vs Offset Corrected Hall Voltage, No Outliers
10-3
3
2
1
0
-1
-2
-3
-4
Bhallcalib - Bhallnom (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)