SLAC Magnetic Measurements
Hall Probe Calibration

Header:
SLAC Magnetic Measurements
Date: 01-12-2016
Time: 15:24:18

Project: LCLS
Device Type: Hall probe
Data Type: Y
Serial Number: SENTRON-441
Run Number: 100
Measurement Type: HPCS
Operator: YL
Comment: Sentron441, voltmeter PC 71027, Voltage standart 5.999895V; Run1

Current(A) T(C) Case T-V Est. Field(T) Voltage Voltage-T-Corr Field

Parameters:
INPUT-FILE-DIR =S:\MagData\LCLS\Hall probe\Sentron-441\HPCS-100\
INPUT-FILE-NAME =hpcs-dat.001
POLY-FIT-ORDER =10
NUM-SIG-OUTLIER =2
NOM-CALIB-CONST =0.2
MAX-B-NMR-FIT =1.5


Hall Probe Temperature
Thall (C)
Bnmr (T)
19.75
19.7
19.65
19.6
19.55
19.5
19.45
19.4
19.35
19.3
19.25
-1.5
-1
-0.5
0
0.5
1
1.5


Reference Hall Probe
0.02
0.015
0.01
0.005
0
-0.005
-0.01
-0.015
-0.02
Bref - Bnmr (T)
-1.5
-1
-0.5
0
0.5
1
1.5
Bnmr (T)


Vhall vs Bnmr, Hall Probe Offset Voltage
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals
10^-5
3
2
1
0
-1
-2
-3
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


Vhall vs Bnmr, Hall Probe Offset Voltage, No Outliers
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected, No Outliers
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals, No Outliers
10^-5
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


(Calibrated Field - Nominal Hall Field) vs Offset Corrected Hall Voltage, No Outliers
10^-3
2
1.5
1
0.5
0
-0.5
-1
-1.5
-2
Bhallcalib - Bhallnom (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)