SLAC Magnetic Measurements

EPU Analysis
––––––––––––

Parameters:
INPUT–FILE–DIR =C:\Magdata\Delta Superpose Quadrants\
INPUT–FILE–NAME =superpose–quadrants.dat
INPUT–FILE–TYPE =ZBXYZH
CORR–REQUIRED =0
GAMMA =26627.1
NOM–LAMBDA–U =0
NOM–K–VALUE =0
NOM–LAMBDA–R =0
NUM–POLES =60
NUM–END–POLES =4
CELL–LENGTH =3.126


Bx, By, Bz vs Zm
Bx (T)
By (T)
Bz (T)
1
0.5
0
−0.5
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
Zm Measurement Position (m)


Bx and By vs Z
6
18
30
43
55
Pole
Bx
By
Bx, By (T)
Z (m)
1
0.8
0.6
0.4
0.2
0
−0.2
−0.4
−0.6
−0.8
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1


Bx vs Z With Fitted Peaks And Zeros
6
19
31
43
56
Pole
1
0.5
0
−0.5
−1
Bx (T)
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z (m)


By vs Z With Fitted Peaks And Zeros
6
18
30
43
55
Pole
1
0.5
0
−0.5
−1
By (T)
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z (m)


Abs(Fitted Peak Bx) vs Z, Excluding Ends
6
12
19
25
31
37
43
50
56
Pole
0.92
0.91
0.9
0.89
0.88
0.87
0.86
Abs(Peak Bx) (T)
Peak Fields: Ave = 0.883729 T, RMS = 0.009959 T
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)


Abs(Fitted Peak By) vs Z, Excluding Ends
6
12
18
24
30
37
43
49
55
Pole
0.92
0.91
0.9
0.89
0.88
0.87
0.86
Abs(Peak By) (T)
Peak Fields: Ave = 0.894479 T, RMS = 0.011120 T
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)


Bx Peak And Zero Field Spacing vs Z, Excluding Ends
6
12
19
25
31
37
43
50
Pole
Peaks
Zeros
Bx Peak And Zero Field Spacing (m)
0.0166
0.0165
0.0164
0.0163
0.0162
0.0161
0.016
0.0159
0.0158
Peak Field Spacing: Ave = 0.016156 m, RMS = 0.000144 m
Zero Field Spacing: Ave = 0.016156 m, RMS = 0.000056 m
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)


By Peak And Zero Field Spacing vs Z, Excluding Ends
6
12
18
24
30
37
43
49
Pole
Peaks
Zeros
By Peak And Zero Field Spacing (m)
0.0166
0.0165
0.0164
0.0163
0.0162
0.0161
0.016
0.0159
0.0158
Peak Field Spacing: Ave = 0.016156 m, RMS = 0.000151 m
Zero Field Spacing: Ave = 0.016153 m, RMS = 0.000066 m
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)


Bx Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^{0}
10^{-1}
10^{-2}
10^{-3}
10^{-4}
10^{-5}
10^{-6}
0
1
2
3
4
5
6
7
8
9
10


By Field Harmonics
|An|
|Bn|
Absolute Value Of An, Bn (T)
n
10^{0}
10^{-1}
10^{-2}
10^{-3}
10^{-4}
10^{-5}
0
1
2
3
4
5
6
7
8
9
10


X Trajectory
x 10^-6
6
18
30
43
55
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X Trajectory (m)
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z (m)


Y Trajectory
x 10^-6
6
18
30
43
55
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y Trajectory (m)
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z (m)


XY Trajectory Projection
x 10^-6
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y Trajectory (m)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
X Trajectory (m)
x 10^-6


Phase Relative To Cell Entrance
250
200
150
100
50
0
Phase (rad)
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z (m)


Phase Error At Field Peaks, No Ends
6
12
18
24
30
37
43
49
55
Pole
20
15
10
5
0
−5
−10
Phase Error (deg)
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)
Phase Error: Ave = 0.000000 deg, RMS = 5.906094 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
6
12
18
24
30
37
43
49
55
Pole
960
955
950
945
940
935
930
925
Phase Error (deg)
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z (m)


Re and Im Parts Of Ex(ω), Forward Direction, ω = ω1
90
4e−12
120
60
3e−12
150
30
2e−12
1e−12
180
0
210
330
240
300
270


Re and Im Parts Of Ey(ω), Forward Direction, ω = ω1
90
4e−12
120
60
3e−12
150
30
2e−12
1e−12
180
0
210
330
240
300
270


Angular Number Spectrum, (ph/sec/mrad2/0.1%bw/0.1A), Forward Direction
x 10^17
Angular Number Spectrum (ph/sec/mrad2/0.1%bw/0.1A)
ω / ω1
0
1
2
3
4
5
6
7
8
9
10


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
x 10^{17}
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
ω / $ω_1$
Measured
Ideal
0
1
2
3
4
5
6
7
0.95
0.96
0.97
0.98
0.99
1
1.01
1.02
1.03
1.04
1.05


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
x 10^{15}
Measured
Ideal
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
ω / ω_1
3.5
3
2.5
2
1.5
1
0.5
0
2.96
2.97
2.98
2.99
3
3.01
3.02
3.03
3.04
3.05


Angular Number Spectrum, (ph/sec/mrad^2/0.1%bw/0.1A), Forward Direction
x 10^{14}
Angular Number Spectrum (ph/sec/mrad^2/0.1%bw/0.1A)
ω / $ω_1$
Measured
Ideal
0
1
2
3
4
5
6
7
8
9
10
4.96
4.97
4.98
4.99
5
5.01
5.02
5.03
5.04
5.05