SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 10−14−2010
Time: 14:48:59

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: ECKO7−20−PPM
DATASET Number: 2
Tuning Stage: Fine Tuning
Run Number: 15
Measurement Type: Z Scans
Operator: YL
Comment: back from tunnel; Gap 11.905mm; find Y at min K
Session first run: 15
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\ECKO7−20−PPM\DATASET0002\Fine Tuning\Z Scans\Run 015\bscanz.dat

Temperature (C)
ECKO7−20−PPM:−−> T5 19.98 −−> T2 20.06 −−> T1 20.09 −−> T3 20.08 −−> Air 20.08 −−> T4 20.13

Axes position (m) X:0.041611 Y:0.000382
Initial Hall Probe Zero Measurements:
Vx_0i = 0.001249 V
Vy_0i = −0.003040 V


Bx vs Z
x 10^-3
5
4
3
2
1
0
−1
−2
−3
−4
−5
Bx (T)
2
12
22
Pole
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z Position (m)


By vs Z
2
12
22
Pole
0.4
0.3
0.2
0.1
0
−0.1
−0.2
−0.3
−0.4
By (T)
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z Position (m)


X Trajectory
x 10^-5
1.5
1
0.5
0
−0.5
−1
−1.5
−2
−2.5
X (m)
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z position (m)
2
12
22
Pole


Y Trajectory
x 10^-6
12
10
8
6
4
2
0
−2
Y (m)
2
12
22
Pole
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 3.684389 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
Pole
4
6
8
10
12
14
16
18
20
185
180
175
170
165
160
Phase Error (deg)
−0.08
−0.06
−0.04
−0.02
0
0.02
0.04
0.06
0.08
Z position (m)