SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 02−27−2012
Time: 15:39:40

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−01
DATASET Number: 2
Tuning Stage: Fine Tuning
Run Number: 16
Measurement Type: Z Scans
Operator: YL
Comment: at min K; after second gap adjustment
Session first run: 15
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−01\DATASET0002\Fine Tuning\Z Scans\Run 016\bscanz.dat

Temperature (C)
L143−112000−01:−−> T1 19.99 −−> T2 19.98 −−> T5 19.95 −−> T3 19.97 −−> Air 20.02 −−> T4 19.96

Axes position (m) X:0.030158 Y:0.000200
Initial Hall Probe Zero Measurements:
Vx_0i = 0.001108 V
Vy_0i = −0.003667 V


Bx vs Z
x 10^-3
13
46
80
113
146
180
213
Pole
Bx (T)
Z Position (m)
5
4
3
2
1
0
−1
−2
−3
−4
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 2.766716 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
15
10
5
0
−5
−10
−15
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)