SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 03−02−2012
Time: 11:04:18

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−01
DATASET Number: 2
Tuning Stage: Fine Tuning
Run Number: 27
Measurement Type: Z Scans
Operator: YL
Comment: final scan
Session first run: 25
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−01\DATASET0002\Fine Tuning\Z Scans\Run 027\bscanz.dat

Temperature (C)
L143−112000−01:−−> T1 19.98 −−> T2 19.97 −−> T5 19.94 −−> T3 19.97 −−> Air 19.95 −−> T4 19.95

Axes position (m) X:0.030142 Y:0.000210
Initial Hall Probe Zero Measurements:
Vx_0i = 0.001006 V
Vy_0i = −0.003555 V


Bx vs Z
x 10^-3
6
5
4
3
2
1
0
−1
−2
−3
−4
13
46
80
113
146
180
213
Pole
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = 0.000000 deg, RMS = 2.092444 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
8
6
4
2
0
−2
−4
−6
−8
−10
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)