SLAC Magnetic Measurements
Hall Probe Calibration

Header:
SLAC Magnetic Measurements
Date: 09-17-2015
Time: 08:42:02

Project: LCLS
Device Type: Hall probe
Data Type: Y
Serial Number: SENIS-118-14
Run Number: 6
Measurement Type: HPCS
Operator: YL
Comment: calibration with voltage correction

Current(A) T(C) Case T-V Est. Field(T) Voltage Voltage-T-Corr Field

Parameters:
INPUT-FILE-DIR =S:\MagData\LCLS\Hall probe\SENIS-118-14\HPCS-006\
INPUT-FILE-NAME =hpcs-dat.001
POLY-FIT-ORDER =13
NUM-SIG-OUTLIER =2
NOM-CALIB-CONST =0.2
MAX-B-NMR-FIT =1.5


Hall Probe Temperature
19.9
19.85
19.8
19.75
19.7
19.65
19.6
Thall (C)
-1.5
-1
-0.5
0
0.5
1
1.5
Bnmr (T)


Reference Hall Probe
0.015
0.01
0.005
0
-0.005
-0.01
-0.015
-0.02
Bref - Bnmr (T)
-1.5
-1
-0.5
0
0.5
1
1.5
Bnmr (T)


Vhall vs Bnmr, Hall Probe Offset Voltage
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
1.5
1
0.5
0
-0.5
-1
-1.5
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals
10^-4
1
0.8
0.6
0.4
0.2
0
-0.2
-0.4
-0.6
-0.8
-1
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


Vhall vs Bnmr, Hall Probe Offset Voltage, No Outliers
Measurements
Fit
Offset
Hall Probe Voltage (V)
Bnmr (T)
8
6
4
2
0
-2
-4
-6
-8
-1.5
-1
-0.5
0
0.5
1
1.5


Fit Bnmr vs Vhall Offset Corrected, No Outliers
Measurements
Fit
Bnmr (T)
Offset Corrected Hall Probe Voltage (V)
1.5
1
0.5
0
-0.5
-1
-1.5
-8
-6
-4
-2
0
2
4
6
8


Polynomial Fit Residuals, No Outliers
10^-5
4
3
2
1
0
-1
-2
-3
-4
-5
Bnmr - Bfit (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)


(Calibrated Field - Nominal Hall Field) vs Offset Corrected Hall Voltage, No Outliers
10-3
10
8
6
4
2
0
-2
-4
-6
-8
Bhallcalib - Bhallnom (T)
-8
-6
-4
-2
0
2
4
6
8
Offset Corrected Hall Probe Voltage (V)