SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 04−18−2013
Time: 09:21:03

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: DELTA
DATASET Number: 1
Tuning Stage: Fine Tuning
Run Number: 57
Measurement Type: Z Scans
Operator: YL
Comment: Q2; #5 −1,#55 −1,#91 −1, #109 −50, #118 −2, #89 −50um, #93 −x 50um, #95 +x 50um,#99 +50um, #117 +200
Session first run: 57
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\DELTA\DATASET0001\Fine Tuning\Z Scans\Run 057\bscanz.dat

Temperature (C)
DELTA:−−> T1 19.95 −−> T2 20.07 −−> T5 19.87 −−> T3 19.92 −−> Air 19.98 −−> T4 19.93

Axes position (m) X:0.020133 Y:0.000025
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000674 V
Vy_0i = −0.003767 V


Bx vs Z
Pole
5
18
30
43
55
0.02
0.015
0.01
0.005
0
−0.005
−0.01
−0.015
−0.02
Bx (T)
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z Position (m)


By vs Z
5
18
30
43
55
Pole
0.5
0.4
0.3
0.2
0.1
0
−0.1
−0.2
−0.3
−0.4
−0.5
By (T)
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z Position (m)


X Trajectory
x 10^-6
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
5
18
30
43
55
Pole
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z position (m)


Y Trajectory
x 10^-6
5
18
30
43
55
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−1
−0.8
−0.6
−0.4
−0.2
0
0.2
0.4
0.6
0.8
1
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 6.371645 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
Pole
5
11
18
24
30
36
43
49
55
290
280
270
260
250
240
230
Phase Error (deg)
−0.5
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
0.4
0.5
Z position (m)