SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 10−06−2010
Time: 16:16:17

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: ECKO7−20−PPM
DATASET Number: 2
Tuning Stage: Fine Tuning
Run Number: 2
Measurement Type: Z Scans
Operator: YL
Comment: back from tunnel; find first pole position
Session first run: 2
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\ECKO7−20−PPM\DATASET0002\Fine Tuning\Z Scans\Run 002\bscanz.dat

Temperature (C)
ECKO7−20−PPM:−−> T5 19.99 −−> T2 20.08 −−> T1 20.12 −−> T3 20.09 −−> Air 20.19 −−> T4 20.12

Axes position (m) X:0.038391 Y:0.000353
Initial Hall Probe Zero Measurements:
Vx_0i = 0.001203 V
Vy_0i = −0.002954 V


Bx vs Z
x 10^-3
6
4
2
0
−2
−4
−6
−8
Bx (T)
2
12
22
Pole
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z Position (m)


By vs Z
2
12
22
Pole
0.8
0.6
0.4
0.2
0
−0.2
−0.4
−0.6
−0.8
By (T)
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z Position (m)


X Trajectory
x 10^-5
2
1
0
−1
−2
−3
−4
X (m)
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z position (m)
2
12
22
Pole


Y Trajectory
x 10^-6
14
12
10
8
6
4
2
0
−2
Y (m)
−0.4
−0.3
−0.2
−0.1
0
0.1
0.2
0.3
Z position (m)
2
12
22
Pole



Phase Error: Ave = 0.000000 deg, RMS = 5.952574 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
Pole
4
6
8
10
12
14
16
18
20
180
170
160
150
140
130
120
110
100
90
Phase Error (deg)
−0.08
−0.06
−0.04
−0.02
0
0.02
0.04
0.06
0.08
Z position (m)