SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 10−23−2012
Time: 11:46:24

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−04
DATASET Number: 3
Tuning Stage: Fine Tuning
Run Number: 6
Measurement Type: Z Scans
Operator: YL
Comment: tuning
Session first run: 5
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−04\DATASET0003\Fine Tuning\Z Scans\Run 006\bscanz.dat

Temperature (C)
L143−112000−04:−−> T1 19.96 −−> T2 19.95 −−> T5 19.93 −−> T3 19.95 −−> Air 19.86 −−> T4 19.93

Axes position (m) X:0.029932 Y:0.000210
Initial Hall Probe Zero Measurements:
Vx_0i = 0.001028 V
Vy_0i = −0.003240 V


Bx vs Z
x 10^-3
13
46
80
113
146
180
213
Pole
4
2
0
−2
−4
−6
−8
−10
−12
−14
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 3.558279 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
450
400
350
300
250
200
150
100
50
0
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)