SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 10−31−2012
Time: 13:35:57

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−04
DATASET Number: 3
Tuning Stage: Fine Tuning
Run Number: 8
Measurement Type: Z Scans
Operator: YL
Comment: tuning; second gap adjustment
Session first run: 8
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−04\DATASET0003\Fine Tuning\Z Scans\Run 008\bscanz.dat

Temperature (C)
L143−112000−04:−−> T1 19.97 −−> T2 19.96 −−> T5 19.96 −−> T3 19.96 −−> Air 19.88 −−> T4 19.96

Axes position (m) X:0.029928 Y:0.000252
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000988 V
Vy_0i = −0.003171 V


Bx vs Z
x 10^-3
13
46
80
113
146
180
213
Pole
4
2
0
−2
−4
−6
−8
−10
−12
−14
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
3
2.5
2
1.5
1
0.5
0
−0.5
−1
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 3.254368 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
120
100
80
60
40
20
0
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)