SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 11−05−2012
Time: 15:50:32

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−04
DATASET Number: 3
Tuning Stage: Fine Tuning
Run Number: 13
Measurement Type: Z Scans
Operator: YL
Comment: at min K
Session first run: 12
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−04\DATASET0003\Fine Tuning\Z Scans\Run 013\bscanz.dat

Temperature (C)
L143−112000−04:−−> T1 20.00 −−> T2 19.98 −−> T5 19.97 −−> T3 19.98 −−> Air 19.96 −−> T4 19.98

Axes position (m) X:0.029928 Y:0.000239
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000942 V
Vy_0i = −0.003246 V


Bx vs Z
x 10^-3
4
2
0
−2
−4
−6
−8
−10
−12
−14
13
46
80
113
146
180
213
Pole
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 2.630505 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
5
0
−5
−10
−15
−20
−25
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)