SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 08−29−2012
Time: 15:45:27

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−15
DATASET Number: 6
Tuning Stage: Fine Tuning
Run Number: 36
Measurement Type: Z Scans
Operator: YL
Comment: check trajectories shims glued
Session first run: 34
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−15\DATASET0006\Fine Tuning\Z Scans\Run 036\bscanz.dat

Temperature (C)
L143−112000−15:−−> T1 20.10 −−> T2 20.09 −−> T5 20.04 −−> T3 20.09 −−> Air 20.06 −−> T4 20.07

Axes position (m) X:0.030235 Y:0.000296
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000932 V
Vy_0i = −0.003109 V


Bx vs Z
x 10^-3
6
4
2
0
−2
−4
−6
−8
Bx (T)
13
46
80
113
146
180
213
Pole
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 2.879289 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
15
10
5
0
−5
−10
−15
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Phase Error (deg)
Z position (m)