SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 09−21−2012
Time: 09:21:34

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−20
DATASET Number: 8
Tuning Stage: Fine Tuning
Run Number: 8
Measurement Type: Z Scans
Operator: YL
Comment: find Y at min K
Session first run: 8
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−20\DATASET0008\Fine Tuning\Z Scans\Run 008\bscanz.dat

Temperature (C)
L143−112000−20:−−> T1 20.07 −−> T2 20.07 −−> T5 20.02 −−> T3 20.07 −−> Air 20.04 −−> T4 20.05

Axes position (m) X:0.029874 Y:0.000285
Initial Hall Probe Zero Measurements:
Vx_0i = 0.000963 V
Vy_0i = −0.003300 V


Bx vs Z
x 10^-3
3
2
1
0
−1
−2
−3
−4
13
46
80
113
146
180
213
Pole
Bx (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
2
1.5
1
0.5
0
−0.5
−1
−1.5
−2
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)



Phase Error: Ave = −0.000000 deg, RMS = 3.592513 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
25
20
15
10
5
0
−5
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)