SLAC Magnetic Measurements

Planar Insertion Device Analysis

SLAC Magnetic Measurements
Date: 04−18−2012
Time: 10:53:49

Project: LCLS
Device Type: Undulator
Data Type:
Serial Number: L143−112000−32
DATASET Number: 5
Tuning Stage: Fine Tuning
Run Number: 17
Measurement Type: Z Scans
Operator: YL
Comment: tuning; fourth gap iteration
Session first run: 17
Measurement Device x:
Measurement Device y: $SENTRON_4$41

Data File: s:\magdata\LCLS\Undulator\L143−112000−32\DATASET0005\Fine Tuning\Z Scans\Run 017\bscanz.dat

Temperature (C)
L143−112000−32:−−> T1 19.98 −−> T2 19.97 −−> T5 19.94 −−> T3 19.97 −−> Air 19.87 −−> T4 19.95

Axes position (m) X:0.030225 Y:0.000341
Initial Hall Probe Zero Measurements:
$Vx_0i$ = 0.001051 V
$Vy_0i$ = −0.003471 V


Bx vs Z
x 10^-3
6
4
2
0
−2
−4
−6
Bx (T)
13
46
80
113
146
180
213
Pole
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


By vs Z
13
46
80
113
146
180
213
Pole
1.5
1
0.5
0
−0.5
−1
−1.5
By (T)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z Position (m)


X Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
1
0.5
0
−0.5
−1
−1.5
−2
−2.5
−3
−3.5
X (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)


Y Trajectory
x 10^-6
13
46
80
113
146
180
213
Pole
8
7
6
5
4
3
2
1
0
−1
Y (m)
−2.5
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
2.5
Z position (m)




Phase Error: Ave = −0.000000 deg, RMS = 4.321259 deg


Phase Error Relative To Nominal Radiation Wave At Field Peaks, No Ends
13
46
80
113
146
180
213
Pole
40
35
30
25
20
15
10
5
0
−5
−10
Phase Error (deg)
−2
−1.5
−1
−0.5
0
0.5
1
1.5
2
Z position (m)